

01 Why choose Moduleo

What sets us apart 04
LayRed engineered vinyl 05

02 Designed to fit life

Strong core Beautiful design 06

03 Collection-overview

Collection-overview 08
Wood 10
Tiles 16

04 Accessories

Installation 22 Finishing 24 Maintenance 27

05 More about Moduleo

Sustainability 30
Retailer activation 32
Roots & Moods 33

# Why choose Moduleo



# What sets us apart

#### Cleverly designed

We strive for stylish, clever and high-quality flooring solutions that don't just look great, but make your life more comfortable as well. From strength and softness to acoustics and warmth, every aspect of your floor is designed and manufactured with care.

#### Challenging all the senses

We go beyond the obvious and don't limit ourselves to traditional colours, patterns, materials, shapes, horizontal surfaces or spaces. We dare to play, combine and inspire. And not just in our designs. Reflection, gloss and texture are all optimised for your wellbeing too. Because we are all about creating exceptional, multisensorial spatial experiences.



#### lifetime warranty

# We are on the planet's side


We're aware of our floors' impact on the planet. And we are working diligently to limit it. By designing them to last a lifetime and producing them more consciously. Right here in Belgium, using as much green energy as we possibly can. By recycling them over and over again. In our own in-house recycling plant, reusing nothing but old vinyl click floors collected through Recover, our Take Back program. Because we are on the planet's side. And in it for the long run.

# LayRed engineered vinyl flooring with integrated underlay and easy click method

Our LayRed collection is built to make your floor update as easy as possible. Extra strong and easier to place. No demolishing or levelling needed. It's your go-to renovation floor. A drill? No need for it. A dust mask? Not this time.

# One plank, twelve layers

- ✓ Extra strong
- ✓ Easy-click system
- ✓ Beautiful design
- ✓ Integrated acoustic underlay (up to 22dB ∆Lw)



#### **Performance**

- 1 Twinguard PU Lacquer
- 2 Wear layer
- 3 Design & print layer
- 4 Design & print layer
- 5 Acoustic layer

#### Strength

- 6 Compact layer
- 7 Glassfibre
- 8 Light weight core
- 9 Light weight core
- 10 Glassfibre


#### Comfort

- 11 Compact layer
- 12 Integrated underlay

# Designed to fit your life




A splash of water in the bathroom, a splatter of ketchup in the kitchen or a book slipping out of your hands in the bedroom, it's a part of life. But homes are meant to be lived in, right? That's why our floors are built to last and keep up with your way of living.



The subtle grooves of real oak? You'll feel them. The cloud-like colour changes in concrete? You'll see them. The matt look that comes with a sandstone finish? Yes, you'll experience that as well. A natural look and feel, that's our goal. And so, we design our floors with all of your senses in mind.

Whether you're walking around in heels, sneakers or barefoot, you are in for a treat either way. Our floors don't just feel warm and comfortable, they soak up the sound of your footsteps as well. Installing underfloor heating or cooling? Go ahead. Our floors can handle it.



# Standard planks

### Large planks



<b>LayRed</b> Herringbone	Thickness (mm)	Embossing	Click- system	Dimensions (cm)	Use classification	Bevel	Waterproof	Warranty
Herringbone (12 designs)	6	in register & standard	Unizip	63,00 x 12,60	23   33	4-sided, refined	yes	Residential: Lifetime Commerical: 5 years*

<b>LayRed</b> Wood	Thickness (mm)	Embossing	Click- system	Dimensions (cm)	Use classification	Bevel	Waterproof	Warranty
Standard plank (16 designs)	6	standard	Uniclic	131,70 x 18,90	23   33	4-sided, refined	yes	Residential: Lifetime Commerical: 5 years*
Large plank (24 designs)	6	in register	Uniclic	149,40 × 20,90	23   33	4-sided, refined	yes	Residential: Lifetime Commerical: 5 years*

# 8 tile designs, 18 colours, 2 sizes

#### Large tiles

#### Standard tiles





н	
н	ack
н	Signature red back
н	re r
н	natu
н	Sig

LayRed Tiles	Thickness (mm)	Embossing	Click- system	Dimensions (cm)	Use classification	Bevel	Waterproof	Warranty
Standard tile (8 designs)	6	standard	Uniclic	61,00 × 30,30	23   33	4-sided, refined	yes	Residential: Lifetime Commerical: 5 years*
Large tile (12 designs)	6	standard	Uniclic	85,60 x 42,80	23   33	4-sided, refined	yes	Residential: Lifetime Commerical: 5 years*



Herringbone planks



<b>LayRed</b> Herringbone	m²	pcs	m²	pcs	Dimensions
	/ box	/ box	/ pallet	/ pallet	(cm)
Herringbone	0,79	10	85,75	108	63,00 x 12,60

#### Blackjack Oak



#### **Country Oak**



#### Classic Oak



24844

#### **Laurel Oak**



51104 51914 51230 51282

#### Sierra Oak



Standard planks



<b>LayRed</b>	m²	pcs	m²	pcs	Dimensions
Wood	/ box	/ box	/ pallet	/ pallet	(cm)
Standard plank	1,99	8	95,52	48	

#### Blackjack Oak



#### Classic Oak



#### Midland Oak



Collection overview

15





<b>LayRed</b>	m²	pcs	m²	pcs	Dimensions
Wood	/ box	/ box	/ pallet	/ pallet	(cm)
Large plank	1,87	6	97,24	52	149,40 x 20,90

#### **Country Oak**



#### Laurel Oak



#### **Mountain Oak**



#### Sierra Oak




# Standard Tiles



<b>LayRed</b>	m²	pcs	m²	pcs	Dimensions
Stone	/ box	/ box	/ pallet	/ pallet	(cm)
Standard tile	1,85	10	74,00	40	

#### York Stone



#### Volterra



46919

#### **Jetstone**



46934

#### Cantera




19

# Large tiles



<b>LayRed</b>	m²	pcs	m²	pcs	Dimensions
Stone	/ box	/ box	/ pallet	/ pallet	(cm)
Large tile	2,20	6	105,60	48	85,60 x 42,80

#### York Stone



#### Millstone



#### 46200

#### Nublo



#### Silky Satin



46920

#### Luzerna




46299



#### Installation

20

#### 1 Integrated underlay



Moduleo LayRed is a smart flooring solution that's easy to install.
The planks and tiles can be fitted using a simple, fast click system.
What's more, Moduleo LayRed comes with an integrated underlay.
No hassle for you.

#### Finishing

#### 2 Skirtings



Your floors and walls are bound to meet. So why not make it a smooth transition? Pick your favourite skirting to complete the look.

#### 3 Profiles



Elevate your space with our versatile waterproof profile, crafted for a sleek and refined finish. Choose between our colour matched profiles or our metal profiles.


#### 4 Staircovers



Transform your staircase effortlessly with stair covers.

#### Maintenance

#### 5 Keep it clean



Accessories

Take good care of your Moduleo LayRed floor and you will enjoy it for a lifetime.

# moduleo ...

22

## Installation

#### Vinyl floor with built-in underlay

The Moduleo LayRed integrated underlay is attached to the product. It ensures easier and quicker installation, better sound dampening (up to 22dB  $\Delta$ Lw) and better levelling of uneven surfaces. Crunching sounds due to underlying dirt or sand grains are fully absorbed.

#### Combine wood & stone to create unique spaces

Enjoy the warmth of wood in the living area and the look of luxury vinyl tiles in the kitchen. Moduleo LayRed planks and tiles are perfectly compatible, guaranteeing you a seamless transition.

#### Uniclic® Fast, easy & reliable

Our angle-angle click system offers the best technical performance on the market: the click ensures a super strong and water resistant joint connection and an easy, convenient installation.



#### **Unizip®** Smarter clicking. Faster placing.

The Moduleo LayRed integrated underlay is attached to the product. It ensures easier and quicker installation, better sound dampening and better levelling of uneven surfaces. Crunching sounds due to underlying dirt or sand grains are fully absorbed.



#### A true benefit

- ✓ Patented technology by Unilin technologies
- ✓ No A& B plank,
- ✓ Installation benefits: quick & intuitive

moduleo

Or download installation instructions here: www. installandclean.com/en/ moduleo

Scan to watch the

Unizip install video





# Finishing

#### Colour matched skirtings

		700	
		•	
		•	
		_	







Scotia VSCOT
<ul><li>✓ Perfectly matching colour</li><li>✓ Waterproof</li><li>✓ 100% recyclable</li></ul>


#### Standard skirting

- ✓ Perfectly matching colour

#### ✓ Waterproof ✓ 100% recyclable

✓ Waterproof

#### Paintable & white skirtings







	length mm	width mm	height mm
Scotia			
345508	2400	19	19
✓ Multi purpose surface: can be left white or painted ✓ Waterproof ✓ 100% recyclable			
Medium skirting			
345506	2400	13	58
<ul> <li>✓ Multi purpose surface: can be left white or painted</li> <li>✓ Waterproof</li> <li>✓ 100% recyclable</li> </ul>			
High skirting			
345507	2400	15	80
✓ Multi purpose surface: can be left white or painted			

length mm

2400

width mm

13

height mm

#### Colour matched profiles

		length mm	width mm	height mm
	For 3 applications VPL	1930	46	17
	✓ Perfectly matching colour ✓ Waterproof			
L	i-in-1 profile: Jse it as an adapter, expansion or end profile			

#### Metal profile



	length mm	width mm	height mm	
Expansion profile	2000	34	7	
<b>Silver</b> 344166 <b>Black</b> 344167				
Adapter profile	2000	38	7	
<b>Silver</b> 344168 <b>Black</b> 344169				
End profile	2000	24	7	
Silver 344170 Black 344171				

- ✓ Scratch resistant top layer✓ For residential and commercial environments

#### **MSK Adhesive**



		Piece			P	ack		
Finishing Tool	length mm	width mm	height mm	pc / pack	length mm	width mm	height mm	
MSK Adhesive	49	49	225	12	213	160	240	_

- $\checkmark$  Developed for installation of Moduleo accessories  $\checkmark$  High elasticity and final strength

Box


width

height

#### Stair covers that match your floor.

Transform your staircase effortlessly with stair covers, made of real floor planks. No staircase adjustments needed—budget-friendly and easily installed with the in-built click profile. Elevate your interior with a harmonious blend of style and durability.

#### Stair cover Bullnose Colour matched



Box

width

Piece

width

length



		Piece			E	Зох	
	length mm	width mm	height mm	pc / box	length mm	width mm	height mm
Bullnose STD	1296	117	54	2	1307	128	65
Bullnose XL	1474	137	54	2	1484	148	65



Number of steps	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Amount of packages Staircovers	1	1	2	2	3	3	4	4	5	5	6	6	7	7	8	8
Number of floor planks <b>STD</b>	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Amount of packages floor planks <b>STD</b>	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
Number of floor planks <b>XL</b>	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Amount of packages floor planks <b>XL</b>	1	1	1	1	1	1	2	2	2	2	2	2	3	3	3	3

#### Stair cover Straight Colour matched

Straight STD	1296	5	16	2	2	8		2		129	97	1	63		36	
Straight XL	1474	1	18	2	2	8		2		14	74	1	86		36	
Number of steps	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Amount of packages Staircovers	1	1	2	2	3	3	4	4	5	5	6	6	7	7	8	8
Number of floor planks STD	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Amount of packages floor planks STD	1	1	1	1	2	2	2	2	3	3	3	3	4	4	4	4
Number of floor planks <b>XL</b>	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
Amount of packages floor planks <b>XL</b>	1	1	1	2	2	2	3	3	3	4	4	4	5	5	5	6

Piece

width

length







**Doormat** 


length mm width mm

Piece

height mm

Sand Grey 345287 Ash Grey 345307 Carbon Grey 345308

Entrance mat small



**Sand Grey** 345311 **Ash Grey** 345312 Carbon Grey 345313

✓ Optimum protection of your Moduleo floor ✓ Effectively trap dirt, mud and debris

# Maintenance

#### Floor care kit



Floor care kit	pc / pack	length mm	width mm	he
Box with 6 Moduleo Floor Care Kits 344626	6	158	81	310

Maintenance



Daily cleaner
Box with 12 bottles (12 x 1000 ml) 344627

 $\checkmark\,$  All-in-one maintenance box for comprehensive floor care  $\checkmark\,$  Optimized for effective use

- ✓ Highly effective✓ Protects your floor's beautiful original character
- ✓ Developed for Moduleo floors

unodieo NENSM CLEANE
CLANE

Intensive cleaner  Box with 12 bottles (12 x 1000 ml)					
	Intensive	cleaner			
	Box with	2 bottles (12	2 x 1000 m	nl)	

- Removes tenacious dirt and old protective layers
   Protects your floor's beautiful original character

eight ım

Piece

Piece

width

width

mm

height

height

mm

length

pc /

pack

pc / pack

Spot cleaner

Box with 8 bottles (8 x 100 ml) 344629

- ✓ Removes even the most persistent stains
- ✓ Gentle for your floor
- ✓ Developed for Moduleo floors

# Matching Accessories Overview

Productname	Decostrip	Scotia	Skirting	Profile	Bullnose	Bullnose XL	Straight	Straight XL
Ordering code	DECOSTRIP	VSCOT	VSK	VPL	STAIR BUL STD	STAIR BUL XL	STAIR ST ST	STAIR STR XL
Dimension (mm)	2400 x 25 x 7	2400 x 19 x 19	2400 x 13 x 58	1930 x 46 x 17	1296 x 162 x 28	1474 x 182 x 28	1296 x 117 x 54	1474 x 137 x 54
Wood								
Blackjack Oak	X	X	X	Χ	X		X	
Classic Oak	X	Х	Х	Х	X		Х	
Midland Oak	X	X	X	X	X		X	
Country Oak	X	Х	X	Х		X		X
Laurel Oak	Х	X	X	Х		X		Х
Mountain Oak	X	X	X	Χ		X		Х
Sierra Oak	X	X	X	X		X		Х
Tiles								
Cantera	X	X	X	X				
Jet Stone	X	X	X	X				
Luzerna	X	X	Χ	×				
Millstone	X	Х	Х	×				
Nublo	X	X	X	Х				
Silky Satin	X	X	Χ	Х				
York Stone	Χ	Χ	Χ	X				




# Technical Specifications

EN 12667         0,047 m². K/W           Formaldehyde group         EN 717-1         E1           Acoustic insulation         EN ISO 717-2         up to 22dB ΔLw / up to 10dB ΔLlin           Castor chair resistance         EN ISO 4918         No damage to wearlayer, no delamination           Stain resistance         EN 438-2         Very good           Light fastness         EN ISO 105-B02         ≥ 6           Underfloor heating         EN 12524         Suitable, max 27°C           Residential lifetime warranty /	Product information		
EN ISO 24346   Omm	Product norm	EN 16511	Compliant
New   New	evel of use	EN ISO 10874	23 - 33
Size & packaging	Total thickness	EN ISO 24346	6 mm
Size & packaging	Vear layer PUR treatment		Twinguard®
EN ISO 24542   149,4 x 20,9 cm	otal weight g/m²	EN ISO 23997	8050
Secret   S	Size & packaging		
EN ISO 24542   85,6 x 42,8 cm	Planks Large	EN ISO 24342	149,4 x 20,9 cm
EN ISO 24542   61 x 30,3 cm	lanks Standard	EN ISO 24342	131,7 x 18,9 cm
EN ISO 24342   65 x 12,6 cm	iles Large	EN ISO 24342	85,6 x 42,8 cm
Specific to the process of the pr	iles Standard	EN ISO 24342	61 x 30,3 cm
Specybox - 1,991 m²	lanks Herringbone	EN ISO 24342	63 x 12,6 cm
10 pcs/box - 0,794 m³	Box planks Large	-	6 pcs/box - 1,873 m²
- 6 pcs/box - 2,198 m²  lox tiles Standard - 10 pcs/box - 1,848 m²    10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 1,848 m²   10 pcs/box - 2,198 m²   10 pcs	ox planks Standard	-	8 pcs/box - 1,991 m²
Test results  Teratch resistance  EN 16094  EN 16094  EN 1897  DIN 51130  EN 150 24543-1  Invariance  EN 150 23999  EN 150 2458  EN 150 4918  EN 0 damage to wearlayer, no delamination tain resistance  EN 438-2  Very good  ight fastness  EN 150 105-B02  ≥ 6  EN 12524  EN 125	ox planks Herringbone	-	10 pcs/box - 0,794 m²
Est results  cratch resistance  EN 16094  ≤ MSR-82 ≤ MSR-B2  Vear group classification  EN 660-2  Group T  Jip resistance  EN 13893  DS  Jip restraint  DIN 51130  R10  Norm: ≤ 0,20mm  Norm: ≤ 0,20mm  Norm: ≤ 0,20mm  Norm: ≤ 1,00mm  Jimensional stability  EN ISO 23999  Norm: ≤ 1 mm  Jimensional stability  EN ISO 23999  Norm: ≤ 0,25 %  Average measured production value: ≤  0,1 mm   Normal dehyde group  EN 12667  O,047 m³. K/W  Jornaldehyde group  EN 150 717-2  Up to 22dB ΔLw / up to 10dB ΔLlin  No damage to wearlayer, no delamination  tain resistance  EN 438-2  Very good  Jornalderfloor heating  EN 12524  Suitable, max 27°C  Residential lifetime warranty / Commercial: 5 years – on request up to 15	ox tiles Large	-	6 pcs/box - 2,198 m²
EN 16094  ≤ MSR-A2 ≤ MSR-B2  Vear group classification  EN 660-2  EN 13893  DS  Illip restraint  DIN 51130  EN 150 24343-1  Norm: ≤ 0,20mm  unriture leg resistance  ISO 16581  No cracks, no damage  unriture leg resistance  EN 1SO 23999  Norm: ≤ 1 mm  Norm: ≤ 0,25 %  Average measured production value: ≤  0,1 mm   hermal resistance R  EN 12667  O,047 m². K/W  ormaldehyde group  EN 150 717-2  EN 150 717-2  Up to 22dB ΔLw / up to 10dB ΔLlin  No damage to wearlayer, no delamination  train resistance  EN 438-2  Very good  Inderfloor heating  Varranty years  EN 12524  EN 12524  EN 12524  EN 12524  EN 150 15 BO2  ER sidential lifetime warranty / Commercial: 5 years - on request up to 15	Sox tiles Standard	-	10 pcs/box - 1,848 m²
EN 16094   SMSR-B2	est results		
EN 13893   DS	cratch resistance	EN 16094	
Ilip restraint  DIN 51130  R10  R10  R10  R10  R10  R10  R10	Vear group classification	EN 660-2	Group T
Iso 24343-1  Norm: ≤ 0,20mm  Unitive leg resistance  Iso 16581  No cracks, no damage  Uniting  EN ISO 23999  Norm: ≤ 1 mm  Norm: ≤ 0,25 %  Average measured production value: ≤  0,10 mm   Normaldehyde group  EN 12667  O,047 m². K/W  Ormaldehyde group  EN 717-1  E1  Coustic insulation  EN ISO 717-2  Up to 22dB ΔLw / up to 10dB ΔLlin  Astor chair resistance  EN 438-2  Very good  Inderfloor heating  Varranty years  EN 12524  Residential lifetime warranty /  Commercial: 5 years - on request up to 15	lip resistance	EN 13893	DS
ISO 16581 No cracks, no damage  EN ISO 23999 Norm: ≤ 1 mm  Norm: ≤ 0,25 % Average measured production value: ≤  0,1]  hermal resistance R  EN 12667 0,047 m². K/W  formaldehyde group  EN 717-1  E1  E1  Locoustic insulation  EN ISO 717-2 up to 22dB ΔLw / up to 10dB ΔLlin  Tastor chair resistance  EN 438-2 Very good  Ight fastness  EN ISO 105-B02  EN 12524  Suitable, max 27°C  Residential lifetime warranty / Commercial: 5 years – on request up to 15	lip restraint	DIN 51130	R10
EN ISO 23999  Norm: ≤ 1 mm  Norm: ≤ 0,25 % Average measured production value: ≤  0,1] hermal resistance R  EN 12667  O,047 m². K/W  ormaldehyde group  EN 717-1  E1  coustic insulation  EN ISO 717-2  up to 22dB ΔLw / up to 10dB ΔLlin  castor chair resistance  EN 438-2  Very good  ight fastness  EN ISO 105-B02  ≥ 6  Inderfloor heating  Varranty years  EN ISO 23999  Norm: ≤ 1 mm  Norm: ≤ 0,25 % Average measured production value: ≤  0, in the light i	tesidual indentation	EN ISO 24343-1	Norm: ≤ 0,20mm
Dimensional stability       EN ISO 23999       Norm: ≤ 0,25 % Average measured production value: ≤  0,1 of 20 measured production value: ≤  0,2 of 20 measu	urniture leg resistance	ISO 16581	No cracks, no damage
Average measured production value: ≤  0,: hermal resistance R  EN 12667  O,047 m². K/W  formaldehyde group  EN 717-1  E1  En ISO 717-2  up to 22dB ΔLw / up to 10dB ΔLlin  fastor chair resistance  EN ISO 4918  No damage to wearlayer, no delamination  frain resistance  EN 438-2  Very good  ight fastness  EN ISO 105-B02  ≥ 6  Inderfloor heating  FN 12524  Varranty years  Average measured production value: ≤  0,:  0,047 m². K/W  En ISO 28999  Average measured production value: ≤  0,:  0,047 m². K/W  En ISO 105-B0  EN ISO 105-B0  ≥ 6  Suitable, max 27°C  Residential lifetime warranty / Commercial: 5 years – on request up to 15	Curling	EN ISO 23999	Norm: ≤ 1 mm
EN 717-1  E1  Locoustic insulation  EN ISO 717-2  up to 22dB ΔLw / up to 10dB ΔLlin  Locoustic insulation  EN ISO 4918  No damage to wearlayer, no delamination  retain resistance  EN 438-2  Very good  ight fastness  EN ISO 105-B02  EN 12524  Varranty years  EN 12524  Suitable, max 27°C  Residential lifetime warranty /  Commercial: 5 years – on request up to 15	Dimensional stability	EN ISO 23999	Norm: ≤ 0,25 % Average measured production value: ≤  0,10  %
EN ISO 717-2 up to 22dB ΔLw / up to 10dB ΔLlin  castor chair resistance EN ISO 4918 No damage to wearlayer, no delamination  train resistance EN 438-2 Very good  ight fastness EN ISO 105-B02 ≥ 6  Inderfloor heating EN 12524 Suitable, max 27°C Residential lifetime warranty / Commercial: 5 years – on request up to 15	hermal resistance R	EN 12667	0,047 m². K/W
EN ISO 4918  No damage to wearlayer, no delamination frain resistance  EN 438-2  Very good  ight fastness  EN ISO 105-B02  EN 12524  Varranty years  EN 12524  Suitable, max 27°C  Residential lifetime warranty / Commercial: 5 years - on request up to 15	ormaldehyde group	EN 717-1	E1
train resistance EN 438-2 Very good  ight fastness EN ISO 105-B02 ≥ 6  Inderfloor heating EN 12524 Suitable, max 27°C Residential lifetime warranty / Commercial: 5 years – on request up to 15	coustic insulation	EN ISO 717-2	up to 22dB ΔLw / up to 10dB ΔLlin
ight fastness EN ISO 105-B02 ≥ 6 Inderfloor heating EN 12524 Suitable, max 27°C  Residential lifetime warranty / Commercial: 5 years - on request up to 15	Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination
Underfloor heating EN 12524 Suitable, max 27°C  Residential lifetime warranty / Commercial: 5 years – on request up to 15	tain resistance	EN 438-2	Very good
Varranty years Residential lifetime warranty / Commercial: 5 years – on request up to 15	ight fastness	EN ISO 105-B02	≥ 6
Commercial: 5 years – on request up to 15	Inderfloor heating	EN 12524	Suitable, max 27°C
Sevel technology 4 edge micro bevel	Varranty years		Residential lifetime warranty / Commercial: 5 years – on request up to 15 years
	Bevel technology	<del></del> -	4 edge micro bevel

The warranty covers manufacturing defects and premature wear in the event of normal use. Unlin reserves the right to change or amend any written information withou notice. Ensure the latest information is being consulted by referring to the website wherever all rights for technical improvements. Photographic images are not representative due to variations in colour printing. The representative samples shown are sectional definitions. For full design representation, please visit the website.

# On the planet's side. In it for the long run.



Our planet is facing a huge challenge. And we are taking our responsibility. How? By producing our floors more consciously. Designing them to last a lifetime. And when they finally do wear out, we recycle them. Over and over again. Because today's throwaway culture isn't ours. We are in it for the long run. And our floors are too.

## Made in Belgium. Powered by nature.

Our floors are designed and made right here in Belgium. Why? To keep transportation journeys short and the footprint of our products low. That's why green energy is our go-to power source too. Today, 60% of our sites in Belgium are powered by our own wind turbines and solar panels. Tomorrow, that part has to be bigger. Even if it's just 0,1 %. We're determined to keep moving forward.

#### Built to last.

Moduleo stands behind the quality of our products with an unparalleled commitment: a lifetime warranty. We assure you that when you choose Moduleo, you're not just selecting flooring; you're investing in lasting quality and peace of mind. Relax and breathe easy, made possible by our tireless innovation in scratch and stain resistance, as well as water resistance.

#### Recycling on repeat.

We took matters into our own hands when it comes to recycling. Moduleo floors are 100% recyclable and in our in-house recycling facility, we process old vinyl floors and reuse them to make new ones. It doesn't even matter whose floor it is. Yours, our own or our competitor's, we recycle them all. Over and over again. We have even set up a recycling program by the name 'Recover' to get our hands on it.















# Retailer activation



#### Discover our new room visualiser

We've revamped our room visualiser with you in mind, focusing on efficiency and userfriendliness. Now it's a win-win for both the end consumer and retailers. It streamlines the decision-making process, enhances customer engagement, and supports a more efficient and effective sales strategy.

Millstone 46200

**Galtymore Oak** 86218

Design strip Off Black


# Moods

#### **Creative designs** Your play

Looking for something different? Feeling creative? Our Moods collection is your playground. The geometric shapes, graphic patterns and powdery new pastels are yours to have fun with.



35



# Roots

#### Cleverly designed **Unique living**

Our Roots collection is as diverse and vivid as nature itself. From warm classics like oak and walnut to serene, natural stones and playful terrazzo. You're bound to find a floor that fits your unique way of living.

# LayRed

Strong core Beautiful design

**Brochure** | For professional use

